

Cape Cod

Finished Wood Siding

ESTIMATING INFORMATION

SIDING COVERAGE FACTORS		FASTENERS & ACCESSORIES	
4" Profiles	1 SF = 4.17 LF	Nails	2 1/2" - 5 Lb Box 900 LF (single nailed 16" O.C.)
6" Profiles	1 SF = 2.46 LF	<i>Stainless Steel</i>	2 1/2" Coils 300 LF (single nailed 16" O.C.)
8" Profiles	1 SF = 1.85 LF	Grades:	3 1/4" - 5 Lb Box 225 LF (double nailed 16" O.C.)
6" Hidden Fastener Profiles	1 SF = 2.64 LF	304 - Standard	3 1/4" Coils 150 LF (double nailed 16" O.C.)
Board & Batten	1"x10" / 1"x2" = 1.33 LF	316 - Req. for "Extreme Exposure Conditions"	<i>4", 6" & 8" Rabetted Bevel are Single</i>
	1"x10" / 1"x3" = 1.20 LF	Staples	Hidden Fastener Profiles 3,300 LF/Box, 660 LF/Minor Box
	1"x8" / 1"x2" = 1.85 LF	Touch Up Paint	Approx. 1 Lt /1,000 LF of Siding
		Laths	1 bundle required for 200 SF of siding
		Strapping	For 16" O.C, 1.0 LF per 1 SF of siding For 12" O.C. 1.2 LF per 1 SF of siding

GENERAL INFORMATION

CCS color number & name as well as sample reference numbers are required when ordering

Siding and trims are shipped in random odd and even lengths, 4'-16'

Specific length requests are subject to availability and price surcharge - Contact Cape Cod office for details

Small custom color orders are subject to a set up charge - Contact Cape Cod office for details

Please refer to Cape Cod Installation instructions for proper installation procedures

Brushed texture available in all profiles

Cape Cod touch up paint and fasteners are required to maintain warranty

For siding and trim installation on structures that are less than 10 meters away from an open body of water ("Extreme Exposure Conditions") the Siding must be pressure treated for the Warranty to be valid. It is also recommended that in all high moisture conditions that pressure treated siding and trims be used.

PLEASE NOTE - The information above is to be used as a guideline only. Quantities required may vary depending on each installation application.